

GOT CRACKS?

v2.0 (with DATA)



HORIZONTAL



VERTICAL



DIAGONAL





Nathan Toothman, P.E.
CEO & Principal Engineer
BS Civil Engineering - University of Colorado
MBA - Chaminade University



Tiffany Toothman
COO & Co-Founder
BS Civil Engineering - USC
BA Physics - Whittier College



Our Mission: Everyone has Someone they Trust with Home Purchase & Repair Decisions

REMOTE CONSULTATIONS



Randy Miller, E.I.T.
Foundation Inspector
BS Civil Engineering -
Purdue University



Kurt Katzenberger, E.I.T.
Foundation Inspector
BS Civil Engineering - Cal Poly
MS Geotechnical Engineering - Cal Poly




Rohith Palle, E.I.T.
Foundation Inspector
MS Construction Mgt., California State U.
BS Civil Engineering, CBIT

ON-SITE FOUNDATION INSPECTIONS

ABOUT US

— HORIZONTAL CRACKS

CAUSE: REBAR RUSTING



MINOR/EARLY STAGES




MAJOR/ADVANCED



CONTRIBUTING FACTORS:

- FOUNDATION IN WET & SALTY SOILS
- LEAKING WATER SOFTENERS
- IRRIGATION LEAKS & CONSTANT WETNESS / GROUNDWATER
- CONSTRUCTION FLAW & REBAR TOO CLOSE TO THE FORM




— HORIZONTAL CRACKS



DATA LEGEND

- No HC
- 1 to 10'
- 11' to 40'
- Over 40' HC

HORIZONTAL CRACKS – REPAIR OPTION 1



Surface Inward Repair

The overview of the procedure is that the cracked areas are chipped away, the rebar is then either cleaned or replaced and then special epoxies and mortar are used to seal and patch the area.

BUDGETARY REPAIR COSTS

- **\$400 PER LINEAR FT (+/- 30%) FOR LONG DISTANCES**
- **\$600 PER LINEAR FT (+/- 30%) FOR SHORT DISTANCES**

HORIZONTAL CRACKS - REPAIR OPTION 2



Partial Foundation Replacement

- Original foundation stem wall is jackhammered out & supported along the way
- Epoxy coated vertical & horizontal steel reinforcing bar dowels are installed into the remaining bottom portion of the foundation
- Concrete forms are installed & poured with concrete

BUDGETARY REPAIR COSTS

- **\$700 PER LINEAR FT (+/- 30%) FOR LONG DISTANCES**
- **\$1,000 PER LINEAR FT (+/- 30%) FOR SHORT DISTANCES**

DIAGONAL CRACKS (& RELATED INDICATIONS)

Most Likely Cause: differential movement / settlement



Foundation



Exterior



Walls



Ceiling

Other Possible Indications



Sloping Floors




Baseboard Gaps



Sticking Doors & Windows

Note: These are things agents can look for in homes & reports

DIAGNOSING VERTICAL & DIAGONAL CRACKS



**TOTAL DIFFERENTIAL ACROSS
THE HOUSE (INCHES)**

	0-1"
	1-2"
	2-3"
	3-4"
	4-5"
	>5"


CAUSES OF DIFFERENTIAL SETTLEMENT

MOST COMMON



Expansive Soils

Expansive soils will swell when wet and contract when dry and this active movement causes the foundation to shift



Lateral Sliding/Soil Creep

Caused by slow downward movement of expansive soils under the influence of gravity and the effect of moisture changes.



Poor Fill Compaction

Where soils are not adequately compacted, they can compress under a foundation load.



Consolidation

Landfill areas where it moves the first 30 years then settles out.

LEAST COMMON



Impact from Trees

Root systems can expand and can draw moisture from the soil beneath the foundation causing settlement & large roots can push up foundations.



Seismic Activity

Vibration from seismic activity during major earthquakes



Soil Erosion

Hillside locations, poor surface drainage, leaks or other underground water movements.



Insufficient Footers



Sometimes footers are either nonexistent, designed too small for the current loads or not built to the design at the time and hence have inadequate bearing capacity.



DIAGNOSIS & REPAIR (if required)

DIAGNOSED VIA FLOOR LEVEL SURVEY

(1 INCH PER 20 FT IS STANDARD TOLERANCE
EXAMPLE: 50 FT LONG HOUSE = 2.5 INCHES)



UNDERPINNING ELEMENTS EVERY 4 – 6 FT @ \$3-4K PER LOCATION



VERTICAL CRACKS



TYPICAL CAUSES

- **Expansive soils** combined with **shallow foundations**
- Lack of rebar (pre mid 1940's)
- Seismic/earthquake activity
- Foundation settlement

VERTICAL - 'SMALL' (approx 1/8" to 1/4")

Epoxy Injection is the typical repair

- approx \$500 per crack (+/- 30%)
- Sometimes just mark & monitor



Repair Process



Repair Completed


VERTICAL - 'MEDIUM' (approx 1/4" to 3/4")



Plate & Epoxy Repair Process

- Injection of a structural epoxy or mortar combined with a steel plate (or rebar stitches) which will span the crack and are anchored into the foundation on either side
- Budgetary price range of \$1,000/crack (+/- 30%)

VERTICAL - LARGE (approx 3/4" plus separation)



TYPICAL REPAIR PROCESS

- Localized underpinning with concrete and rebar to reinforce this area below and on the sides
- Budgetary price range of \$2K - \$3K per crack +/- 30%

THANKS!!



HORIZONTAL



VERTICAL



DIAGONAL

